

Product information RSW - RSW 50-04/2 M

Industrial Connecting Solutions:Circular Connectors:7/8", M23 Connectors:7/8" Connectors:Overmolded Single Ended 7/8" Cordsets:Connectors:RSW

http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256289-256290-276527-276528-248893/en/RSW_05-02/uistate

Name RSW

6.80 mm

5 x 0.50 mm²

16 x 0.2 mm

none



	Actuator/sensor cordset, 7/8" male connector, right angle version, with self-locking threaded joint and molded cable, PVC cable, orange, 5 poles, 2 meters.
Delivery informations	
Availability	available
Product description	
Туре	RSW 50-04/2 M
Order No.	98580
Description	Actuator/sensor cordset, 7/8" male connector, right angle version, with self-locking threaded joint and molded cable, PVC cable, orange, 5 poles, 2 meters.
Number of contacts	5
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance
Mechanical data	
Type of plug-in contact	Male connector
Design of housing	angled
Thread	7/8"
Design of electrical connection	connector 7/8 inch
LED display present	×
Environmental conditions Control Contr	
Environmental temperature	-40 °C 90 °C
Dograp of protection (ID) mounted	1000

71	
Design of housing	angled
Thread	7/8"
Design of electrical connection	connector 7/8 inch
LED display present	×
Environmental conditions	
Environmental temperature	-40 °C 90 °C
Degree of protection (IP), mounted	IP68
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	TPU, self-extinguishing
Contact material	CuZn
Contact material - Surface refinement	silver-plated and 0.3 microns gold-plated
Knurled screw / nut material	PA
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	9 A at 40°C, UL and notice derating
Nominal voltage	240 V
Rated voltage	250 V
Test voltage	1.5 kV eff./60 s
Insulation resistance	>1 GΩ
Approvals	
RoHS 2002/95/EG compliant	RoHS 2002/95/EG
Cable	
Cable length	2 m
Cable description	Cable for sensors and actuators
Color of jacket	orange
Material of outer jacket	PVC



Flame resistant according to standard

Outer diameter of the cable Nominal diameter of the cable

Construction of conductor




 $Industrial\ Connecting\ Solutions: Circular\ Connectors: 7/8",\ M23\ Connectors: 7/8"\ Connectors: Overmolded\ Single\ Ended\ 7/8"\ Cordsets: Connectors: RSW$

 $http://www.e-catalog.beldensolutions.com/link/57078-24228-256281-256289-256290-276527-276528-248893/en/RSW_05-02/uistate$

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

